

DUCT AIR LEAKAGE TESTER DALT 6900

Automated commercial duct air leakage testing

Kanomax introduces a new Duct Air Leakage Tester (DALT) for commercial duct systems. The instrument provides step-by-step test configuration and automated leakage testing based on the SMACNA HVAC Air Duct Leakage Test Manual. The instrument is designed for easy transport to the job with a small footprint and stair walker dolly.

DUCT LEAKAGE TESTER SPECIFICATIONS		
Duct static pressure range	+/- 10 in. w.g. (+/- 2500 Pa)	
Volumetric flow range	2 to 377 CFM (4 to 640 m3/h)	
Testing surface area (at 4 in.w.g.)	Up to 10500 sq. ft.	
Temperature range	-4 to 140 °F (-20 to 60 °C)	
Weight	165 lbs. (75kg)	

^{*}Specifications are subject to change without notice...



FEATURES AND BENEFITS

- Step-by-step test configuration and automated leakage testing based on the SMACNA Test Manual.
- Automatically calculates leakage percent per AABC standards.

DISTRIBUTED BY:

- Capable of both positive and negative duct leakage tests.
- Easy transport to the job with a small footprint.
- Option to connect two DALTs for bigger projects.

0000/1000		13:30
0.7	200262	
Limit		
70.2 °F	29.9 inHg	4.000 inH2O
	Limil	0.008262 Limit 0.049246 Pass

KANOMAX USA, INC. 219 US HWY 206, ANDOVER, NJ 07821 USA TEL: 973-786-6386

FAX: 973-786-7586

E-MAIL: SALES@KANOMAX-USA.COM URL: WWW.KANOMAX-USA.COM

Copyight © 2019 Kanomax USA, Inc.